

Section 1- Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product Name: Pumps that include 54V Lithium Ion Battery

Model No.: XC2202MA, XC2202MB, XC2202ME, XC2204MA, XC2204MB, XC2204ME, XC2302SA, XC2302SB, XC2302SE, XC2304SA, XC2304SB, XC2304SE, XC2402MA, XC2402MB, XC2402ME, XC2404MA, XC2404MB, XC2404ME, XC2502BA, XC2502BB, XC2502BE, XC2504BA, XC2504BB, XC2504BE, SC1201MA, SC1201MB, SC1201ME, SC1201MBS, SC1201MES

Other means of identification

Synonyms: None

Recommended use and restrictions on use

Recommended Use: LITHIUM ION BATTERIES

Uses advised against: No information available

Information of the supplier

Supplier Name: Enerpac Tool Group

Address: 648 N Plankinton Ave, 4th Floor, Milwaukee, WI 53203

Phone: (262) 293-1500

Fax: (262) 293-7040

E-mail: enerpac.orders@enerpac.com

Emergency Contact (24h): 1-888-533-7762 (US and CA), 1-813-708-1083 (All other countries)

Section 2 – Hazards Identification

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) this product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word: Danger

Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold.

Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Black

Physical State Solid

Odor Odorless

Precautionary Statements - Prevention	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product
Precautionary Statements - Response	IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention
Precautionary Statements - Storage	Store locked up
Precautionary Statements - Disposal	Dispose of contents/container to an approved waste disposal plant
Hazards not otherwise classified (HNOC)	Not applicable
Unknown Toxicity	-
Other information	May be harmful if swallowed Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Interactions with Other Chemicals	No information available.

Section 3 – Composition/Information on Ingredients

Chemical Name	CAS Number	Weight-%	Trade Secret
Cobalt lithium manganese nickel oxide	18224-95-1	41	-
Graphite	7782-42-5	22	-
Lithium hexafluorophosphate	21324-40-3	16	-
Copper foil	7440-50-8	11	-
Aluminum foil	7429-90-5	5	-
Polyethylene (PE)	9002-88-4	1	-
Polyvinylidene fluoride (PVDF)	24937-79-9	1	-
Carboxymethyl cellulose	9004-32-4	1	-
Styrene-Butadiene rubber 1500 (SBR)	9003-55-8	1	-
Carbon black	1333-86-4	1	-

* The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4 – First-aid Measures

General Advice	First aid is upon rupture of sealed battery. Eye contact: If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area. Skin contact: Wash off immediately with soap and plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction. Inhalation: Remove to fresh air. If symptoms persist, call a physician. Get medical attention immediately if symptoms occur. Ingestion: Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician. Self-protection of the first aider: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).
Most important symptoms and effects, both acute and delayed	Most important symptoms and effects: Itching. Coughing and/ or wheezing.
Indication of any immediate medical	Notes to Physician: Treat symptomatically. May cause sensitization of susceptible persons.

attention and special treatment needed	
--	--

Section 5 – Fire-fighting Measures

Suitable extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing Media	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific Hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	Sensitivity to Mechanical Impact: No. Sensitivity to Static Discharge: No.
Protective Equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Personal Precautions: Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Other Information: Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.
Methods and material for containment and cleaning up	Methods for Containment: Prevent further leakage or spillage if safe to do so. Methods for cleaning up: Pick up and transfer to properly labeled containers.

Section 7 – Handling and Storage

Precautions for safe handling	Handling: In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.
Conditions for safe storage, including any incompatibilities	Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Products: Strong acids. Strong oxidizing agents. Strong bases.

Section 8 – Exposure Controls and Personal Protection

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Aluminum foil 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	-
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Cobalt lithium manganese nickel oxide 182442-95-1	TWA: 0.02 mg/m ³	-	-

*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value
 OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits
 NIOSH IDLH: Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls	Engineering Measures: Showers Eyewash stations Ventilation systems.
Individual protection measures, such as personal protective equipment	Eye/Face Protection: If splashes are likely to occur. Wear safety glasses with side shields (or goggles). None required for consumer use. Skin and Body Protection: Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

Section 9 - Physical and Chemical Properties

Physical Properties	Physical state: Solid	
	Appearance: Black and Prismatic	
	Color: Black	
	Odor: Odorless	
	Odor Threshold: No information available	
Chemical Properties:		
Property	Values	Remarks/ Method
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known

Flammability (solid, gas)	No data available	None known
Flammability Limit in Air	No data available	-
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	130°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	0.00001	None known
Explosive properties	No data available	-
Oxidizing Properties	No data available	-

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

Section 10 - Stability and Reactivity

Reactivity	No data available.
Chemical stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids. Strong oxidizing agents. Strong bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 - Toxicological Information

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.
---------------------	--

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Sodium carboxymethyl cellulose 9004-32-4	-	-	> 5800 mg/m ³ (Rat) 4 h

Information on toxicological effects	Symptoms: Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Sensitization: May cause sensitization of susceptible persons. May cause sensitization by skin contact. Mutagenic Effects: No information available. Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Carbon black 1333-86-4	A3	Group 2B	-	X
Cobalt lithium manganese nickel Oxide 182442-95-1	A3	Group 1 Group 2B	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS). Kidney. Liver. Lungs. Heart.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The values which are on the right are calculated based on chapter 3.1 of the GHS document.	ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-dust/mist)
--	--

Section 12 - Ecological Information

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Carbon black 1333-86-4	-	-	-	24h EC50: > 5600 mg/L

Persistence and Degradability	No information available.
Bioaccumulation	No information available
Other adverse effects	No information available.

Section 13 – Disposal Considerations

Waste treatment methods

Disposal methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or

Enerpac Tool Group

Tel: (262) 293-1500 <http://www.enerpac.com>

otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

Chemical Name	RCRA	RCRA - D Series Wastes	RCRA - U Series Wastes	OSHA
-	-	-	-	-

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Aluminum foil 7429-90-5	Ignitable powder
Cobalt lithium manganese nickel oxide 182442-95-1	Toxic

Section 14 – Transport Information

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions, Packing instruction 965, section I A (2021-2022 Edition).
- The International Air transport Association (IATA) Dangerous Goods Regulations, Packing instruction 965, section I A (63rd Edition, 2022).
- The International Maritime Dangerous Goods (IMDG) Code (Amendment 40-20 Edition).
- The US Hazardous Materials Regulation 49CFR (Code of Federal Regulations).
- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries.
- Proper shipping name and UN ID number: LITHIUM ION BATTERIES, UN No.: UN3481.

Our products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, and should be transported as Class 9 hazardous material. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria.

Test results of the UN Recommendation on the Transport of Dangerous Goods

Manual of Test and Criteria (38.3 Lithium battery)			
No.	Test items	Test results	Remark
T1	Altitude simulation	Pass	-
T2	Thermal test	Pass	-
T3	Vibration	Pass	-
T4	Shock	Pass	-
T5	External short circuit	Pass	-
T6	Impact	Pass	-
T7	Overcharge	Pass	-
T8	Forced discharge	Pass	-

The following information is provided for domestic and international transportation:

DOT regulations:		
UN Classification (Transport Hazard class):	9	
UN number:	3481	
Packing group:	II	
UN Proper shipping name(technical name):	LITHIUM ION BATTERIES	
Marine pollutant(Y/N)	N	
Label:	Class 9 (Lithium batteries)	
Land transportation ADR/RID (cross-broder):		
ADR/RID class:	9 Miscellaneous dangerous substances and articles	
Danger code(Kemler):	9	
UN-Number:	3481	
Packaging group:	II	
Marine pollutant(Y/N):	N	
Label:	Class 9 (Lithium batteries)	
Description of goods:	LITHIUM ION BATTERIES	
Sea transport IMDG:		
Class or division:	Class 9	
UN Number:	3481	
Label:	Class 9 (Lithium batteries)	
Packaging group:	II	
EMS Number:	F-A, S-I	
Marine pollutant(Y/N):	N	
Propper shipping name:	LITHIUM ION BATTERIES	
Air transport ICAO-TI and IATA-DGR:		
Class or division:	Class 9	
UN Number:	3481	
Label:	Class 9 (Lithium batteries)	
Packaging group:	II	
Marine pollutant(Y/N):	N	
Propper shipping name:	LITHIUM ION BATTERIES	

Section 15 - Regulatory Information

International Inventories

TSCA: Complies

DSL: All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Aluminum foil	7429-90-5	5	1.0
Cobalt lithium manganese nickel oxide	182442-95-1	41	1.0 0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Cobalt lithium manganese nickel oxide 182442-95-1	-	X	-	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Aluminum foil 7429-90-5	-	-	-

US State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

This product contains the following Proposition 65 chemicals.

Enerpac Tool Group

Tel: (262) 293-1500 <http://www.enerpac.com>

Chemical Name	California Proposition 65
Carbon black - 1333-86-4	Carcinogen
Cobalt lithium manganese nickel oxide - 182442-95-1	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Graphite 7782-42-5	X	X	X	-	-
Aluminum foil 7429-90-5		X		X	
Carbon black 1333-86-4	X	X	X	-	X
Lithium nickel cobalt manganese oxide 182442-95-1	X	-	X	X	X

International Regulations
Mexico
National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphite 7782-42-5 (22%)	-	Mexico: TWA= 2 mg/m ³
Aluminum foil 7429-90-5 (5%)	-	Mexico: TWA= 10 mg/m ³
Carbon black 1333-86-4 (1%)	-	Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³
Cobalt lithium manganese nickel oxide 182442-95-1(41%)	-	Mexico: TWA 0.2 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada
WHMIS Hazard Class

Non-controlled

Section 16 - Other Information

NFPA	Health Hazards 1	Flammability 0	Instability 1	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 4	Flammability 0	Physical Hazard 1	

Revision Note: No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

--End of Safety Data Sheet--